Lydia® VOICE SOLUTIONS

Lydia® VoiceWear

For voice-directed work

With Lydia® VoiceWear, topsystem introduces a new innovative product in human engineering! Thanks to integrated speakers and microphone, pickers no longer need a headset while picking by Voice. This increased freedom of movement creates a distinct advantage in a warehouse where heavy lifting is part of the daily routine.

All the technical components for voice-directed tasks are combined in Lydia® VoiceWear, providing optimal protection against environmental hazards. With Lydia® VoiceWear wearing cables have become obsolete.

Lydia® VoiceWear provides equal comfort for both men and women. It only takes seconds to put on this compact vest, thus reducing prep time to start the job.

Your advantage:
Hands free,
Eyes free

topsystem VOICE SOLUTIONS

Lydia® VOICE SOLUTIONS

In addition to the speakers and microphone components, topsystem's Voxter® is integrated into Lydia® VoiceWear. The Voxter® is a mobile voice device, designed and manufactured by topsystem and optimized for use with Pick by Voice.

Your advantages at a glance:

- Lydia® VoiceWear is extremely easy to put on or take off.
- Compact and reliable protection of all technical Voice components.
- No external cables on the upper body of the picker.
- Optimum mobility for the users.
- Optional voice output via speaker or ear piece.
- Interior part of VoiceWear is removable for easy washing.
- Comfortable to wear for men and women alike.

Product Profile

General:

Wearing system:	supported by straps with 3-point buckle
Connector:	optimized for Voxter® Elite Edition
Inner material:	mesh, washable at 30°C / 86°F, Oekotex norm 100, product class I
Outer material:	Cordura, Oekotex norm 100 Product class II

Size:

Chest strap:	65 cm / 25" - 170 cm / 5.5 ft
Back length:	33 cm / 13"
Shoulder belts:	58 cm / 23"
Weight:	approx. 480 g / approx. 17 oz.

Loudspeaker:
Impedance: 8 ohm
Audio frequency range: 300 – 20000 Hz
Sound pressure: max 101dB

Microphone:
Audio frequency range: 100 – 10000 Hz
Microphone characteristics: super cardioid
Impedance: 2,2k Ohm

topsystem OPTIMIZING PROCESSES

topsystem Systemhaus GmbH
Monnetstraße 24
52146 Würselen
Germany

Telefon: +49.2405.4670-0
Fax: +49.2405.4670-10
E-Mail: info@topsystem.de
Web: www.topsystem.de

2014/11