Lydia® VOICEWEAR

Lydia® VoiceWear®

For maximum freedom of movement

With Lydia® VoiceWear®, topsystem introduces a new innovative product in human engineering! Thanks to integrated speakers and microphone, pickers no longer need a headset while picking by Voice. This increased freedom of movement creates a distinct advantage in a warehouse where heavy lifting is part of the daily routine.

All the technical components for voice-directed tasks are combined in Lydia® VoiceWear®, providing optimal protection against environmental hazards. With Lydia® VoiceWear® wearing cables have become obsolete.

Lydia® VoiceWear® provides equal comfort for both men and women. It only takes seconds to put on this compact vest, thus reducing prep time to start the job.

Your advantage:
Hands free,
Eyes free

Lydia® VOICE

Lydia® VOICEWEAR

In addition to the speakers and microphone components, topsystem's Voxter® can be integrated into Lydia® VoiceWear®. The Voxter® is a mobile voice device, designed and manufactured by topsystem and optimized for use with Pick by Voice.

Your advantages at a glance:

- Lydia® VoiceWear® is extremely easy to put on and take off.
- Compact and reliable protection of all technical voice components.
- No external cables on the upper body of the picker.
- Optimum mobility for users.
- Optional voice output via speaker or ear piece.
- Interior part of VoiceWear® is removable for easy washing.
- Comfortable to wear for men and women alike.

Product Profile

General

Wearing system:	supported by straps
Compatibility:	Voxter® Elite Edition & Standard Mobile Clients
Inner material:	mesh, washable at 30 °C / 86 °F, OEKO-TEX® norm 100, product class I
Outer material:	Cordura, OEKO-TEX® norm 100 product class II
Temperatures:	operating t.: -30 to 50 °C / -22 to 122 °F storage t.: 0 to 50 °C / 32 to 122 °F

Measures

Size:	one-size-fits-all
Weight:	approx. 490 g / approx. 17 oz.

Loudspeaker

Impedance:	8 Ohm
Audio frequency range:	300 – 20,000 Hz
Sound pressure:	max. 101dB

Microphone

Impedance:	2,2 kOhm
Audio frequency range:	100 – 10,000 Hz
Microphone characteristics:	supercardioid

topsystem
OPTIMIZING PROCESSES

topsystem Systemhaus GmbH
Monnetstraße 24
52146 Würselen
Germany

Telefon: +49.2405.4670-0
Fax: +49.2405.4670-10
E-Mail: info@topsystem.de
Web: www.topsystem.de

TEXTILES VERTRAUEN
Geprüft auf Schadstoffe
nach Oeko-Tex® Standard 100

made in Germany

2017/11